

ACRYLIC CONCRETE SEALER

MATERIAL SAFETY DATA SHEET (Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30329

Emergency Telephone Number
(770) 216-9580

Information Telephone Number
(770) 216-9580

MSDS W1
Revision: Feb-07

QUIKRETE® Product Name
ACRYLIC CONCRETE SEALER

Code #
8800

HEALTH			1
FLAMMABILITY			0
PHYSICAL HAZARD			0
PERSONAL PROTECTION			
Safety Glasses, Gloves			

PRODUCT USE: ACRYLIC BASED CURING AND SEALING COMPOUND FOR FRESH OR HARDENED CONCRETE

SECTION II - HAZARD IDENTIFICATION

Route(s) of Entry: Inhalation, Ingestion

Acute Exposure: None known

Chronic Exposure: Repeated or prolonged skin contact may result in mild irritation. Vapor may be an irritant to the respiratory tract. Ingestion may cause irritation to the gastrointestinal tract.

Carcinogenicity: Not applicable

Signs and Symptoms of Exposure: None known

Medical Conditions Generally Aggravated by Exposure: None known

Chronic Exposure: None known

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS No.	PEL (OSHA) Mg/m ³	TLV (ACGIH) mg/m ³
Acrylic Polymer, may contain Propylene Glycol Phenyl Ether	770-35-4	Not Established	Not Established

SECTION IV – First Aid Measures

Eyes: Immediately flush eye thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids. Call physician immediately.

Skin: Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment if irritation or inflammation develops or persists.

Inhalation: Remove person to fresh air. Seek medical help if irritation persists.

Ingestion: Treat symptomatically and supportively. Get medical attention. DO NOT attempt to give anything by mouth to an unconscious person.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Unusual hazards: This water based dispersion can splatter at temperatures above 100°C (212°F). Polymer film can burn once the water has evaporated. Product also contains less than 5 % of a solvent with a Flash Point of 115°C (240°F)

Extinguishing Agents: Use methods appropriate for surrounding fire.

Personal Protective Equipment: For fire fighting, wear self-contained breathing apparatus and full protective gear.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Absorb spillages onto sand, earth or any suitable absorbent material. Sweep up and shovel into waste drums. Wash the spillage area with water. Washings must be prevented from entering surface water drains. Polymer may be separated from water by addition of alum and ferric chloride. Disposal should be in accordance with local, state or national legislation.

NOTE: Spilled emulsion is very slippery. Use care to avoid falls. Latex will leave a film on drying. Remove saturated clothing and wash contacted skin areas with soap and water.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Storage Temperature: 40 – 100°F

Handling/Storage: Avoid extreme temperatures. Protect from freezing. This material should not be spilled, discharged, or flushed into sewers or public waterways. Product contains low level of organic volatiles which could accumulate in the un-vented headspace of drums or bulk storage vessels. Open drums in well-ventilated area, avoid breathing vapors.

SECTION VIII – EXPOSURE CONTROL MEASURES

Engineering Controls: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (30 m/min.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Personal Protection: Wear safety glasses with side shields. Protect against splashing. The use of neoprene gloves is recommended. Gloves of other chemically resistant materials may not provide adequate protection. Clothing protection should be worn. Rubber boots and apron should be worn if exposure is severe. Remove contaminated clothing and launder before reuse.

Other Protective Equipment: Facilities storing or utilizing this material should be equipped with an eyewash facility.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical appearance: Milky white liquid with a slight ether odor
Solubility in Water: Infinitely Dilutable
Viscosity: 1000 cps max.
Melting point: ~30° F (-1°C) water
Boiling point: ~100°C/212°F
Volatile Organic Content (VOC): 32 g/L

SECTION X - REACTIVITY DATA

Stability: This material is considered stable. However, avoid temperatures above 177°C/350°F, the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

Hazardous Decomposition Products: Thermal decomposition may yield acrylic monomers.

Hazardous Polymerization: Will not occur.

Incompatibility: Avoid contact with strong oxidizing agents or strong alkalis.

SECTION XI – TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, Ingestion

Toxicity to Animals:

LD50: Not Available

LC50: Not Available

Chronic Effects on Humans: Not established

Special Remarks on Toxicity: Unlikely to cause harmful effects under recommended conditions of handling and use

SECTION XII – ECOLOGICAL INFORMATION

Ecotoxicity: Not Available

BOD5 and COD: Not Available

Products of Biodegradation: Not available

Toxicity of the Products of Biodegradation: Not available

Special Remarks on the Products of Biodegradation: Ingress to waterways may cause persistent milky turbidity.

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method: For large quantities, place in settling pond and add ferric chloride and lime. Decant water. Dispose of solids in landfill. Emulsion can be incinerated directly under appropriate conditions. Disposal should be in accordance with local, state or national legislation. This product is not classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302).

SECTION XIV – TRANSPORT INFORMATION

DOT/UN Shipping Name: Non-regulated
DOT Hazard Class: Non-regulated
Shipping Name: Non-regulated
Non-Hazardous under U.S. DOT and TDG Regulations

SECTION XV – OTHER REGULATORY INFORMATION

SARA (Title III) Section 313: Not subject to reporting requirements
TSCA (May 1997): All components are on the TSCA inventory list
Federal Hazardous Substances Act: Is a hazardous substance subject to statues promulgated under the subject act
Canadian Environmental Protection Act: Not listed
Canadian WHMIS: Considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This product has been classified according to the hazard criteria of the Controlled Products Regulation (CPR). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

SECTION XVI – OTHER INFORMATION

HMIS-III:

Health –	0 = No significant health risk
	1 = Irritation or minor reversible injury possible
	2 = Temporary or minor injury possible
	3 = Major injury possible unless prompt action is taken
	4 = Life threatening, major or permanent damage possible
Flammability-	0 = Material will not burn
	1 = Material must be preheated before ignition will occur
	2 = Material must be exposed to high temperatures before ignition
	3 = Material capable of ignition under normal temperatures
	4 = Flammable gases or very volatile liquids; may ignite spontaneously
Physical Hazard-	0 = Material is normally stable, even under fire conditions
	1 = Material normally stable but may become unstable at high temps

- 2 = Materials that are unstable and may undergo react at room temp
3 = Materials that may form explosive mixtures with water
4 = Materials that are readily capable of explosive water reaction

Abbreviations:

ACGIH	American Conference of Government Industrial Hygienists
CAS	Chemical Abstract Service
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act
CFR	Code of Federal Regulations
CPR	Controlled Products Regulations (Canada)
DOT	Department of Transportation
IARC	International Agency for Research
MSHA	Mine Safety and Health Administration
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicity Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TWA	Time-weighted Average
WHMIS	Workplace Hazardous Material Information System

Revision #07-01, supersedes all previous revisions

Created: November 29, 2006

Last Updated: February 7, 2007

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.
