



JOINT-LOCK™ HP STONE - BLUESTONE

**HIGH
PERFORMANCE**

1. PRODUCT NAME: JOINT-LOCK HIGH PERFORMANCE
STONE - BLUESTONE

2. ITEM CODE:
98550 - 70 LB. JOINT-LOCK HP STONE

3. MANUFACTURER:
PACKAGE PAVEMENT Co., Inc.
675 Leetown Road, PO Box 408
Stormville, NY 12582
(800) 724-8193
FAX (845) 221-0433
www.packagepavement.com

4. PRODUCT DESCRIPTION:

Joint-Lock HP Stone is a polymer modified stone dust that is specifically designed to complement and enhance any natural stone or paver installation with wide joints. Joint-Lock HP Stone sets and remains hard to resist weed growth, insect mining and erosion. It will resist scouring caused by sweeping, water rinsing and traffic.

Joint-Lock HP Stone is designed specifically to work under conditions that ordinary polymeric sands cannot support. Its unique formulation will allow it to be installed in joints up to three inches wide with superior results. On a properly compacted sub-base, Joint-Lock HP Stone will provide a firm durable surface that stands up very well to foot traffic, sweeping or blowing. Joint-Lock HP Stone will also help prevent the movement of stone pavers.

It is sold in 70 Lb. (31.7kg) bags / 42 per pallet by nurseries, landscape yards, mason material yards and home centers.

5. TECHNICAL DATA:

Complete installation instructions are printed on the Joint-Lock bag. Use Joint-Lock HP Stone for joints from 1/2" to 3 INCHES WIDE. A well compacted, free draining base beneath the pavers is required for optimum effectiveness.

6. INSTALLATION:

Prior to application of Joint-Lock HP Stone, make sure the surface is dry and the paver joints are clean. (CAUTION: Do not apply when stones are damp as the product will bond to the surface of the pavers.) By closely following the steps of the instructions you will ensure that your use of Joint-Lock HP Stone will provide a long lasting and beautiful finish for years to come.

INSTALLATION INSTRUCTIONS



1. CLEAN & DRY STONES / PAVERS

Make sure that the surface of the pavers and the paver joints are free of debris and completely dry before applying Joint-Lock HP Stone. The weather forecast should be rain free for 12 hours after application to ensure optimum bonding and product performance.



2. POUR STONE DUST & SPREAD

Pour Joint-Lock HP Stone evenly over the entire area to be finished. Sweep Joint-Lock HP Stone repeatedly over the joints until they are completely and uniformly filled. For best results fill joints to the full depth of the pavers. **DO NOT USE A FILLER AS IT WILL COMPROMISE THE STRENGTH OF THIS PRODUCT.**



3. COMPACT & SWEEP

Use a gas powered plate compactor to compact the stone between the joints of the pavers. This will ensure all voids are filled. Repeat steps 2 & 3 as necessary. After compaction sweep off all extra stone dust. If pavers are coarse, use a leaf blower on lowest setting to clear sand off the paver surface.



4. THOROUGHLY WET AREA 2X

After surface of pavers is completely free of stone dust, begin to lightly but thoroughly wet the area with water. Allow the water to collect and seep into the paver joints. Wait 10 minutes and repeat this step to ensure proper water penetration. Make sure the paving stones are free of car and foot traffic for 18-24 hours following application of Joint-Lock HP Stone.

7. CAUTION:

KEEP UNUSED JOINT-LOCK HP STONE DRY! Do not apply if rain is forecast within 12 hours of the application or the temperatures are expected to go below freezing. If treating an existing walkway, patio, or previously laid pavers, make sure the joints are clean and free of debris to the base of the paving stones.

8. SAFETY AND HANDLING:

Always wear dust masks, goggles, and gloves while using Joint-Lock HP Stone. If the product comes in contact with eyes, rinse them thoroughly with water. **KEEP OUT OF REACH OF CHILDREN.**

9. WARRANTY:

PACKAGE PAVEMENT warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of this product (as purchased) found to be defective or, at the shipping company's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to PACKAGE PAVEMENT in writing. This limited warranty is issued and accepted in lieu of all other express warranties and excludes liability for consequential damages.