



ECO-FRIENDLY HIGH PERFORMANCE BLACKTOP REPAIR™

1. Product Name:

ECO-FRIENDLY H.P. BLACKTOP REPAIR w/Handle

2. Item Code(s):

102215 - 50 LB. H.P. REPAIR BAG (63/Pallet)
111118 - HP BLACKTOP REPAIR - BULK

3. Manufacturer:

Package Pavement Co., Inc.
675 Leetown Road, PO Box 408
Stormville, NY 12582
PH (800) 724-8193
FAX (845) 221-0433
www.packagepavement.com

4. Product Description:

PACKAGE PAVEMENT® Eco-Friendly High Performance Blacktop Repair with an integrated handle is a specially blended performance grade asphalt and stone cold-patch mixture used for permanently patching potholes and cracks greater than 1" wide in asphalt pavement. It is suitable to use for repairing potholes in roads, driveways and walkways. Eco-Friendly H.P. Blacktop Repair contains an EPA compliant asphalt blend which complies with the clean air guidelines adopted by DE, NJ, CT and NY.

5. Technical Data:

Eco-Friendly HP Blacktop Repair can be successfully applied straight from the bag into a wet, active repair area. Use the "Throw and Roll" technique for the speediest repairs.

6. Installation Instructions:

To maximize the long term success of your repair, the following three steps should be followed:

Note: The maximum area per repair is 9 square feet at a depth of 3".

1 > PREPARE

Sweep and clean area to be filled. Square off the edges of the hole and remove all loose material. Vertical sides will provide a stronger patch.

2 > FILL

Apply at least 1" thick, compacting each 1/2" layer. Fill the hole to a height of 1/2" above the surrounding surface. Patches over 1" thick must be applied in 1/2" lifts which must be adequately compacted before additional material is added.

3 > COMPACT

Roll or tamp the area using a tamper or a roller. The patch may also be covered with plywood or plastic and driven over to increase compaction.



**A VOC COMPLIANT
HIGH PERFORMANCE
ASPHALT COLD PATCH**

7. Caution:

Avoid getting PACKAGE PAVEMENT ECO-FRIENDLY BLACKTOP REPAIR on hands or clothing. For patching use only. Not for use as a blacktop pavement resurfacer. Avoid turning car tires over patch until surface cures. (Approx. 2-3 Days depending on weather conditions.)

PLEASE READ BEFORE USING:

This mixture contains petroleum asphalt which is listed as a potential carcinogen by IARC. Store the container in a well ventilated area. Do not breathe fumes excessively or expose to an open flame. Avoid eye contact or prolonged contact with skin. Wash skin thoroughly with water after handling. In case of eye contact, wash with plenty of water for at least 15 minutes. If irritation persists, consult a physician immediately.

8. Safety and Handling:

Always wear gloves when handling and avoid contact with eyes or mouth. If the product comes in contact with eyes, rinse them thoroughly with water.

KEEP OUT OF REACH OF CHILDREN.

9. Winter/Summer Asphalt Changes:

PACKAGE PAVEMENT modifies the asphalt blend to ensure peak performance year round. Stock rotation, first in, first out, is essential to obtain optimum product cure time and durability.

10. Warranty:

PACKAGE PAVEMENT warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of this product (as purchased) found to be defective or, at the shipping company's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Package Pavement in writing. This limited warranty is issued and accepted in lieu of all other express warranties and excludes liability for consequential damages.

**EASY ON THE ENVIRONMENT
TOUGH ON POTHOLES**

