



ECO-FRIENDLY BLACKTOP PLATE PATCH



ASPHALT PRODUCT SPECS

1. Product Name: 60# BLACKTOP PLATE MIX

2. Item Code: 102606 - (60 LB. - 56 Bags / Pallet)

3. Manufacturer:
 Package Pavement Co., Inc.
 675 Leetown Road, PO Box 408
 Stormville, NY 12582
 (800) 724-8193
 FAX (845) 221-0433
 www.packagepavement.com

4. Product Description:
 PACKAGE PAVEMENT® ECO-FRIENDLY BLACKTOP PLATE MIX is a specially blended mix of high quality asphalt, and blended coarse and fine aggregate used for build-up ramps around metal plates for road repair. It can also be used for patching potholes in roads, driveways and walkways. Can also be used to repair drainage grates, and creating build-up ramps for garage entrances. Ready-to-Use straight from the bag. Requires no heating, mixing, or additions. Patched surfaces are ready for immediate foot traffic after application.

5. Technical Data:
 Complete installation instructions can be found on the PACKAGE PAVEMENT BLACKTOP PLATE MIX bag. Product is designed for surface repair only and not resurfacing.

Bag Yield:
 60 LB. BAG = 4-5 s.f.

6. Installation:
 Installation of PACKAGE PAVEMENT ECO-FRIENDLY BLACKTOP PLATE MIX can be done in **3 EASY STEPS**...

1 > PREPARE

Sweep and clean area to be filled. An inset plate is ideal, but a sufficient build up around the plate will also help with stabilization.

2 > FILL

Apply at least 1" thick, compacting each 1/2" layer. Fill the hole to a height of 1/2" above the surrounding surface. Patches over 1" thick must be applied in 1/2" lifts which must be adequately compacted before additional material is added.

3 > COMPACT

Compact the area with a roller or tamper. The patch may also be covered with plywood or plastic and driven over to increase compaction.

7. Caution:

Avoid getting PACKAGE PAVEMENT BLACKTOP PLATE MIX on hands or clothing. For patching use only. Not for use as a blacktop pavement resurfacer.

PLEASE READ BEFORE USING

This mixture contains petroleum asphalt which is listed as a potential carcinogen by IARC. Store the container in a well ventilated area. Do not breathe fumes excessively or expose to an open flame. Avoid eye contact or prolonged contact with skin. Wash skin thoroughly with water after handling. In case of eye contact, wash with plenty of water for at least 15 minutes. If irritation persists, consult a physician immediately.

8. Safety and Handling:

Always wear gloves when handling and avoid contact with eyes or mouth. If the product comes in contact with eyes, rinse them thoroughly with water.

9. Winter/Summer Asphalt Changes:

To enable peak performance year round, PACKAGE PAVEMENT modifies the asphalt blend to keep the liquid attuned to the season. To ensure that your stock is designed for the current season, rotate it on a regular basis.

KEEP OUT OF REACH OF CHILDREN

10. Warranty:

PACKAGE PAVEMENT warrants this product to be merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of this product (as purchased) found to be defective or, at the shipping company's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Package Pavement in writing. This limited warranty is issued and accepted in lieu of all other express warranties and excludes liability for consequential damages.



**EASY ON THE ENVIRONMENT
TOUGH ON POTHOLES**