



80
40

For best results, keep PLUG-R® between 40 degrees and 80 degrees fahrenheit just before use. These limits assure that PLUG-R will not shatter from cold when hammered into the hole and will not soften from extreme heat. Extreme heat from a closed vehicle, hot storage area or direct sun will cause softness which makes PLUG-R® stick together.



SIZE OF PLUG-R®

SIZE OF PLUG-R	APPROX. DRILL SIZE	BOTTOM DIAMETER	BOTTOM DIAMETER (Metric)	TOP DIAMETER	APPROX. LENGTH	# PER CASE
3/4"	3/4"	3/4"	19 mm.	1"	1-1/2"	512
7/8"	1"	7/8"	22 mm.	1-1/4"	2-3/8"	320
1-1/8"	1-1/4"	1-1/8"	28 mm.	1-1/2"	2-3/8"	176
1-1/4"	1-1/2"	1-1/4"	32 mm.	1-3/4"	3"	112
1-1/2"	1-3/4"	1-1/2"	38 mm.	2"	3"	96
1-3/4"	2"	1-3/4"	44 mm.	2-1/8"	3"	96

CONTAINS:

NAME

CAS#

ASPHALT
RECYCLED RUBBER

8052-42-4
9006-04-6*
61789-96-6*

WAX
MOLD RELEASE
COMPOUND

110-30-5
61790-44-1
61789-30-8
7732-18-5

KEEP OUT OF REACH OF CHILDREN



Select the PLUG-R® that will go three-quarters of the way into the hole before using force. (ex: use 1-1/8" PLUG-R for a 1-1/4" hole)



PLUG-R®'s are packed loose in cases. A special release material is used to keep them from sticking together.



Place a PLUG-R® in the hole, cover with a board and pound in with a hammer.



Then hit the PLUG-R® directly with the hammer to break off any excess asphalt. The PLUG-R® is now part of the pavement.